

1

2

3

4

5

6

7

SPECIFICATIONS

AUTHENTICATION AUTHORITY:	UL	TUV
AUTHENTICATION STANDARD:	UL2251 CSA C22.2 NO.182.2	IEC62196-1
RATED VOLTAGE:	DC 500V	
RATED CURRENT:	120A	
NUMBER OF POLES:	POWER 2, SIGNAL 7	
CABLE CABLE:	POWER 2, SIGNAL 9	
OPERATION TEMPERATURE RANGE:	-40 ~ 60°C	

CONFORMING TO THE EUROPEAN ELV AND RoHS DIRECTIVES

仕様

認証機関	UL	TUV
認証規格	UL2251 CSA C22.2 NO.182.2	IEC62196-1
定格電圧	DC 500V	
定格電流	120A	
極数	POWER 2, SIGNAL 7	
キャブタイヤケーブル	POWER 2, SIGNAL 9	
動作温度範囲	-40 ~ 60°C	

欧州ELV、RoHS指令に対応

SCL	ANGLE
1:1	3

NAME DC CHARGING CONNECTOR / VEHICLE-SIDE CONNECTOR

DC充電コネクタ / 車両側コネクタ

YAZAKI CORPORATION

1

2

3

4

5

6

7